

ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH ISO 14025 AND ISO 21930:2017

SmartEPD-2024-039-0192-01.1

Steri-Coat P



Date of Issue:
Oct 28, 2024

Expiration:
Oct 28, 2029

Last updated:
Oct 28, 2024

General Information	4
Reference Standards	4
Verification Information	5
Limitations, Liability, and Ownership	5
Organization Information	5
Product Information	5
Plants	6
Product Specifications	6
Material Composition	6
Software and LCI Data Sources	7
EPD Data Specificity	8
Renewable Electricity	8
System Boundary	9
Product Flow Diagram	10
Life Cycle Module Descriptions	10
LCA Discussion	10
Results	12
Environmental Impact Assessment	12
Resource Use Indicators	14
Waste and output Flow Indicators	15
Carbon Emissions and Removals	16
Scenarios	17
Transport to the building/construction site (A4)	17
Installation in to the building/construction site (A5)	17
Reference Service Life (B1)	17
Replacement (B4)	17

End of Life (C1 - C4)	18
Interpretation	19
Additional Environmental Information	19
References	19

General Information

Dudick Inc.
1818 Miller Parkway, Streetsboro, OH 44241
800-322-1970
sales@dudick.com dudick.com



Product Name:	Steri-Coat P
Functional Unit:	1 m2 of covered and protected flooring surface for a period of 60 years
Declaration Number:	SmartEPD-2024-039-0192-01.1
Date of Issue:	October 28, 2024
Expiration:	October 28, 2029
Last updated:	October 28, 2024
EPD Scope:	Cradle to grave A1 - A3, A4, A5, B1 - B5, C1 - C4, D
Market(s) of Applicability:	North America

Reference Standards

Standard(s):	ISO 14025 and ISO 21930:2017
PCR:	NSF PCR for Resinous Floor Coatings v.1e Date of issue: December 17, 2018 Valid until: December 17, 2024
PCR review panel:	Contact Smart EPD for more information.
General Program Instructions:	Smart EPD General Program Instructions v.1.0, November 2022

Verification Information

LCA Author/Creator:

 Juan David Villegas |  juan@parqhq.com

EPD Program Operator:

 Smart EPD |  info@smartepd.com |  www.smartepd.com |
 585 Grove St., Ste. 145 PMB 966, Herndon, VA 20170, USA

Verification:

Independent critical review of the LCA and data, according to ISO 14044 and ISO 14071 : **External**

 Ranjani Theregowda |  Smart EPD LLC |  ranjani.theregowda@smartepd.com

Independent external verification of EPD, according to ISO 14025 and reference PCR(s) : **External**

 Ranjani Theregowda |  Smart EPD LLC |  ranjani.theregowda@smartepd.com

Limitations, Liability, and Ownership

Environmental declarations from different programs (ISO 14025) may not be comparable. Comparison of the environmental performance of products using EPD information shall be based on the product's use and impacts at the building level, and therefore EPDs may not be used for comparability purposes when not considering the whole building life cycle. EPD comparability is only possible when all stages of a life cycle have been considered. However, variations and deviations are possible. Example of variations: Different LCA software and background LCI datasets may lead to differences results for upstream or downstream of the life cycle stages declared. The EPD owner has sole ownership, liability, and responsibility for the EPD.

Organization Information

For over fifty years, Dudick has been at the forefront of delivering cutting-edge product development alongside a wealth of technical expertise and experience, offering unparalleled chemical resistant coating solutions on a global scale. As a notable manufacturer of high performance resinous flooring and other coating products, Dudick is dedicated to showcasing its sustainability leadership while recognizing the business value in transparently reporting the comprehensive environmental impacts of its products, spanning from cradle to grave. For additional details on Dudick's product range, visit their website at <https://www.dudick.com>.

Further information can be found at: www.dudick.com

Product Description

This amine cured epoxy coating provides a very tough seamless coating system for high abuse areas. It is an excellent coating for areas requiring protection against the growth of mold, mildew, fungus and bacteria. The unique hybrid binder in Steri-Coat P provides high film integrity, and good chemical resistance required for prolonged substrate protection.

Further information can be found at: <https://www.dudick.com/products/steri-coat/steri-coat-p/>

Product Information

Functional Unit:

1 m2 of covered and protected flooring surface for a period of 60 years

Mass:

0.274 kg

Reference Service Life:

60 Years

Product Specificity:

✗ Product Average

✓ Product Specific

Plants



Dudick - Streetsboro, OH
1818 Miller Parkway, Streetsboro, OH, USA

Product Specifications

Product SKU(s):

123D9811905D

Product Classification Codes:

Masterformat - 09 67 00

EC3 - Finishes -> Flooring -> OtherFlooring

Material Composition

Material/Component Category	Origin	% Mass
Crosslinking agent	USA	<10%
Curing agent	USA	10-30%
Defoamer	DEU	<10%
Dispersing agent	USA	<10%
Epoxy resin	USA	20-40%
Filler, extender	USA	10-30%
Monomer/epoxy resin	USA	0-20%
Pigment	USA	0-20%
Rheology modifier	USA	<10%
Surface additive	USA	<10%

Packaging Material	Origin	kg Mass
plastic pail	USA	0.027

Hazardous Materials

2-ethyl-2-[[[1-oxo-2-propenyl)oxy)methyl]-1 (15625-89-5)

2-Propenoic acid (15625-89-5)

3-propanediyl ester (15625-89-5)

4,4'-(1-methylethyidene)bis (30583-72-3)

4,4'-Isopropylidenediphenol-Epichlorohydrin Copolymer (25068-38-6)

10-diamine (9046-10-0)

Benzyl alcohol (100-51-6)

Bisphenol A-epichlorohydrin-diethylenetriamine copolymer (31326-29-1)

Cycloaliphatic amine (PROPRIETARY)

Cyclohexanedimethanol diglycidyl ether (14228-73-0)

Cyclohexanol (30583-72-3)

Diethylenetriamine (111-40-0)

Isophoronediamine (2855-13-2)

Methyl Ethyl Ketone (78-93-3)

polymer with (chloromethyl)oxirane (30583-72-3)

Polyoxypropylene-2 (9046-10-0)

EPD Data Specificity

Primary Data Year:

2022-2023

Manufacturing Specificity:

- ☒ Industry Average
- ☒ Manufacturer Average
- ☒ Facility Specific

Averaging:

Averaging was not conducted for this EPD

Software and LCI Data Sources

LCA Software:	 SimaPro v. 9.5
LCI Foreground Database(s):	 Ecoinvent v. 3.9.1
LCI Background Database(s):	 Ecoinvent v. 3.9.1


Renewable Electricity

Renewable electricity is used:	No
--------------------------------	----

System Boundary

Production	A1	Raw material supply	✓
	A2	Transport	✓
	A3	Manufacturing	✓
Construction	A4	Transport to site	✓
	A5	Assembly / Install	✓
Use	B1	Use	✓
	B2	Maintenance	✓
	B3	Repair	✓
	B4	Replacement	✓
	B5	Refurbishment	✓
	B6	Operational Energy Use	✓
	B7	Operational Water Use	✓
End of Life	C1	Deconstruction	✓
	C2	Transport	✓
	C3	Waste Processing	✓
	C4	Disposal	✓
Benefits & Loads Beyond System Boundary	D	Recycling, Reuse Recovery Potential	ND

Product Flow Diagram



Life Cycle Module Descriptions

Primary data were collected for the 12 month period starting October 2022 and ending September 2023 to ensure technical, geographical and temporal the representativeness. The products in this study are manufactured at Dudick's production facilities. The manufacturing process entails the addition of pre-weighted ingredients, followed by mixing in the correct sequence to create the desired products. Subsequently, Dudick packages and distributes the finished products to various distribution centers. The process involves the use of grid electricity, heat from natural gas combustion, an process water. Non hazardous waste consisting mainly of packaging material is sent to disposal or recycling.

LCA Discussion

Allocation Procedure

Product packaging was allocated by mass. Allocation of co-products was avoided, to the extent it was possible, based on the guidance given in ISO 14044:2006, 4.3., in ISO 21930 and section 5 of the NSF International PCR for Resinous Floor Coatings. Volumetric allocation was applied to energy and water use at the facility level, as it represents the partition among selling units (using mass or volume production, where appropriate). Dudick, Inc. provided the total volume or mass produced at each facility.

Cut-off Procedure

No cut-off criteria are defined for this study. The system boundary was defined based on relevance to the goal of the study. For the processes within the system boundary, all available energy and material flow data have been included in the model. In cases where no matching life cycle inventories are available to represent a flow, proxy data have been applied based on conservative assumptions regarding environmental impacts.

Data Quality Discussion

The quality of inventory data is evaluated based on several criteria, including precision, completeness, consistency, and representativeness.

Precision and Completeness

- Precision: The inventory data used in this study were either directly measured, calculated, or estimated based on primary data sources, ensuring high precision. Background data from ecoinvent v3.9.1 database also has documented precision to the extent available.

- Completeness: The product system's mass balance and inventory completeness were thoroughly checked. Some exclusions were made in line with the PCR requirements, such as personnel impacts, R&D activities, business travel, secondary packaging, point of sale infrastructure, and the coating applicator. However, no data was intentionally omitted..

Consistency and Reproducibility

- Consistency: Primary data were collected with a similar level of detail, while background data came from the ecoinvent v3.9.1 database. The modeling approach and other methodological choices were applied consistently throughout the model. Default values from the PCR were considered where there was unavailability of primary data.

- Reproducibility: This study ensures reproducibility by providing comprehensive disclosure of input-output data, dataset choices, and modeling approaches. A knowledgeable third party should be able to approximate the results using the same data and modeling methods.

Representativeness

- Temporal: Primary data were collected for the one-year period of October 2022 to September 2023 to ensure the representativeness of post-consumer content.

Secondary data from the ecoinvent v3.9.1 database is typically representative of recent years.

- Geographical: Primary data represent Dudick's production facilities. Where applicable, differences in electric grid mix were considered using appropriate secondary data. The use of country-specific data ensures high geographical representativeness, and proxy data were only used when country-specific data were unavailable.

- Technological: Both primary and secondary data were tailored to the specific technologies studied, ensuring high technological representativeness. Where no direct raw material information was available in the ecoinvent 3.9.1 database, proxies were identified and used.

Results

Environmental Impact Assessment Results

TRACI 2.1
per 1 m2 of covered and protected flooring surface for a period of 60 years.
LCIA results are relative expressions and do not predict impacts on category endpoints, the exceeding of thresholds, safety margins or risks.

Market

Impact Category	Method	Unit	A1A2A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
GWP-total	TRACI 2.1	kg CO2e	1.93	0.153	0.0311	ND	0.901	ND	10.5	ND	ND	ND	ND	0.01	0.119	1.01
ODP	TRACI 2.1	kg CFC11 eq	9.42e-8	2.52e-9	2.32e-11	ND	7.36e-8	ND	4.84e-7	ND	ND	ND	ND	1.65e-10	8.13e-10	6.71e-10
AP	TRACI 2.1	kg SO2 eq	0.0168	0.000818	0.00000934	ND	0.00489	ND	0.088	ND	ND	ND	ND	0.0000536	0.000078	0.000277
EP	TRACI 2.1	kg N eq	0.00445	0.000156	0.000335	ND	0.00362	ND	0.0247	ND	ND	ND	ND	0.0000102	0.0000504	0.0109
POCP	TRACI 2.1	kg O3 eq	0.272	0.0229	0.000157	ND	0.0541	ND	1.47	ND	ND	ND	ND	0.0015	0.00103	0.00435

Abbreviations:

GWP = Global Warming Potential, 100 years (may also be denoted as GWP-total, GWP-fossil (fossil fuels), GWP-biogenic (biogenic sources), GWP-luluc (land use and land use change)), ODP = Ozone Depletion Potential, AP = Acidification Potential, EP = Eutrophication Potential, SFP = Smog Formation Potential, POCP = Photochemical oxidant creation potential, ADP-Fossil = Abiotic depletion potential for fossil resources, ADP-Minerals&Metals = Abiotic depletion potential for non-fossil resources, WDP = Water deprivation potential, PM = Particular Matter Emissions, IRP = Ionizing radiation, human health, ETP-fw = Eco-toxicity (freshwater), HTP-c = Human toxicity (cancer), HTP-nc = Human toxicity (non-cancer), SQP = Soil quality index.

per 1 m2 of covered and protected flooring surface for a period of 60 years.

Tech

Impact Category	Method	Unit	A1A2A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
GWP-total	TRACI 2.1	kg CO2e	1.93	0.153	0.0311	ND	0.901	ND	6.33	ND	ND	ND	ND	0.00667	0.0794	0.673
ODP	TRACI 2.1	kg CFC11 eq	9.42e-8	2.52e-9	2.32e-11	ND	7.36e-8	ND	2.9e-7	ND	ND	ND	ND	1.1e-10	5.42e-10	4.47e-10
AP	TRACI 2.1	kg SO2 eq	0.0168	0.000818	0.00000934	ND	0.00489	ND	0.0528	ND	ND	ND	ND	0.0000357	0.000052	0.000185
EP	TRACI 2.1	kg N eq	0.00445	0.000156	0.000335	ND	0.00362	ND	0.0148	ND	ND	ND	ND	0.0000068	0.0000336	0.00727
POCP	TRACI 2.1	kg O3 eq	0.272	0.0229	0.000157	ND	0.0541	ND	0.884	ND	ND	ND	ND	0.001	0.000684	0.0029

Abbreviations:
GWP = Global Warming Potential, 100 years (may also be denoted as GWP-total, GWP-fossil (fossil fuels), GWP-biogenic (biogenic sources), GWP-luluc (land use and land use change)), ODP = Ozone Depletion Potential, AP = Acidification Potential, EP = Eutrophication Potential, SFP = Smog Formation Potential, POCP = Photochemical oxidant creation potential, ADP-Fossil = Abiotic depletion potential for fossil resources, ADP-Minerals&Metals = Abiotic depletion potential for non-fossil resources, WDP = Water deprivation potential, PM = Particular Matter Emissions, IRP = Ionizing radiation, human health, ETP-fw = Eco-toxicity (freshwater), HTP-c = Human toxicity (cancer), HTP-nc = Human toxicity (non-cancer), SQP = Soil quality index.

Comparisons cannot be made between product-specific or industry average EPDs at the design stage of a project, before a building has been specified. Comparisons may be made between product-specific or industry average EPDs at the time of product purchase when product performance and specifications have been established and serve as a functional unit for comparison. Environmental impact results shall be converted to a functional unit basis before any comparison is attempted. Any comparison of EPDs shall be subject to the requirements of ISO 21930 or EN 15804. EPDs are not comparative assertions and are either not comparable or have limited comparability when they have different system boundaries. EPDs are not comparative assertions and are either not comparable or have limited comparability when they have different system boundaries, are based on different product category rules or are missing relevant environmental impacts. Such comparison can be inaccurate, and could lead to erroneous selection of materials or products which are higher-impact, at least in some impact categories.

Resource Use Indicators

per 1 m2 of covered and protected flooring surface for a period of 60 years.

Market

Indicator	Unit	A1A2A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
RPRE	MJ	0.677	0.0196	0.000682	ND	0.544	ND	3.49	ND	ND	ND	ND	0.00129	0.0025	0.0216
RPRM	MJ	0.421	0.00767	0.000145	ND	4.46	ND	2.14	ND	ND	ND	ND	0.000503	0.000636	0.00448
RPRT	MJ	1.1	0.0273	0.000828	ND	5	ND	5.63	ND	ND	ND	ND	0.00179	0.00313	0.0261
NRPRE	MJ	30.5	2.16	0.0192	ND	13.8	ND	163	ND	ND	ND	ND	0.141	0.533	0.553
NRPRM	MJ	0.0017	0.0000311	0.00000137	ND	0.00189	ND	0.00864	ND	ND	ND	ND	0.00000204	0.00000207	0.0000436
NRPRT	MJ	30.5	2.16	0.0192	ND	13.8	ND	163	ND	ND	ND	ND	0.141	0.533	0.553
ADPF	MJ	3.78	0.303	0.00231	ND	1.49	ND	20.4	ND	ND	ND	ND	0.0198	0.0794	0.065
FW	m3	0.0219	0.000243	0.0000153	ND	0.0362	ND	0.111	ND	ND	ND	ND	0.0000159	0.0000527	0.00049

Abbreviations:

RPRE or PERE = Renewable primary resources used as energy carrier (fuel), RPRM or PERM = Renewable primary resources with energy content used as material, RPRT or PERT = Total use of renewable primary resources with energy content, NRPRE or PENRE = Non-renewable primary resources used as an energy carrier (fuel), NRPRM or PENRM = Non-renewable primary resources with energy content used as material, NRPRT or PENRT = Total non-renewable primary resources with energy content, SM: Secondary materials, RSF = Renewable secondary fuels, NRSF = Non-renewable secondary fuels, RE = Recovered energy, ADPF = Abiotic depletion potential, FW = Use of net freshwater resources, VOCs = Volatile Organic Compounds.

per 1 m2 of covered and protected flooring surface for a period of 60 years.

Tech

Indicator	Unit	A1A2A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
RPRE	MJ	0.677	0.0196	0.000682	ND	0.544	ND	2.09	ND	ND	ND	ND	0.000858	0.00166	0.0144
RPRM	MJ	0.421	0.00767	0.000145	ND	4.46	ND	1.29	ND	ND	ND	ND	0.000335	0.000424	0.00299
RPRT	MJ	1.1	0.0273	0.000828	ND	5	ND	3.38	ND	ND	ND	ND	0.00119	0.00209	0.0174
NRPRE	MJ	30.5	2.16	0.0192	ND	13.8	ND	97.9	ND	ND	ND	ND	0.0943	0.356	0.368
NRPRM	MJ	0.0017	0.0000311	0.00000137	ND	0.00189	ND	0.00519	ND	ND	ND	ND	0.00000136	0.00000138	0.0000291
NRPRT	MJ	30.5	2.16	0.0192	ND	13.8	ND	97.9	ND	ND	ND	ND	0.0943	0.356	0.368
ADPF	MJ	3.78	0.303	0.00231	ND	1.49	ND	12.3	ND	ND	ND	ND	0.0132	0.053	0.0433
FW	m3	0.0219	0.000243	0.0000153	ND	0.0362	ND	0.0664	ND	ND	ND	ND	0.0000106	0.0000351	0.000327

Abbreviations:

RPRE or PERE = Renewable primary resources used as energy carrier (fuel), RPRM or PERM = Renewable primary resources with energy content used as material, RPRT or PERT = Total use of renewable primary resources with energy content, NRPRE or PENRE = Non-renewable primary resources used as an energy carrier (fuel), NRPRM or PENRM = Non-renewable primary resources with energy content used as material, NRPRT or PENRT = Total non-renewable primary resources with energy content, SM: Secondary materials, RSF = Renewable secondary fuels, NRSF = Non-renewable secondary fuels, RE = Recovered energy, ADPF = Abiotic depletion potential, FW = Use of net freshwater resources, VOCs = Volatile Organic Compounds.

Waste and Output Flow Indicators

per 1 m2 of covered and protected flooring surface for a period of 60 years.

Market

Indicator	Unit	A1A2A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
HWD	kg	0.00105	ND	ND	ND	ND	ND	0.00524	ND	ND	ND	ND	ND	ND	ND
NHWD	kg	0.0409	ND	0.0494	ND	ND	ND	0.452	ND	ND	ND	ND	ND	ND	1.61

Abbreviations:
HWD = Hazardous waste disposed, NHWD = Non-hazardous waste disposed, RWD = Radioactive waste disposed, HLRW = High-level radioactive waste, ILLRW = Intermediate- and low-level radioactive waste, CRU = Components for re-use, MFR or MR = Materials for recycling, MER = Materials for energy recovery, MNER = Materials for incineration, no energy recovery, EE or EEE = Recovered energy exported from the product system, EET = Exported thermal energy.

per 1 m2 of covered and protected flooring surface for a period of 60 years.

Tech

Indicator	Unit	A1A2A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
HWD	kg	0.00105	ND	ND	ND	ND	ND	0.00314	ND	ND	ND	ND	ND	ND	ND
NHWD	kg	0.0409	ND	0.0494	ND	ND	ND	0.271	ND	ND	ND	ND	ND	ND	1.07

Abbreviations:
HWD = Hazardous waste disposed, NHWD = Non-hazardous waste disposed, RWD = Radioactive waste disposed, HLRW = High-level radioactive waste, ILLRW = Intermediate- and low-level radioactive waste, CRU = Components for re-use, MFR or MR = Materials for recycling, MER = Materials for energy recovery, MNER = Materials for incineration, no energy recovery, EE or EEE = Recovered energy exported from the product system, EET = Exported thermal energy.

Carbon Emissions and Removals

per 1 m2 of covered and protected flooring surface for a period of 60 years.

Market

Indicator	Unit	A1A2A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
BCRP	kg CO2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
BCEP	kg CO2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
BCRK	kg CO2	0.00181	ND	ND	ND	ND	ND	0.00904	ND	ND	ND	ND	ND	ND	ND
BCEK	kg CO2	-0.00181	ND	ND	ND	ND	ND	-0.00904	ND	ND	ND	ND	ND	ND	ND
BCEW	kg CO2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
CCE	kg CO2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
CCR	kg CO2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
CWNR	kg CO2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND

Abbreviations:

BCRP = Biogenic Carbon Removal from Product, BCEP = Biogenic Carbon Emission from Product, BCRK = Biogenic Carbon Removal from Packaging, BCEK = Biogenic Carbon Emission from Packaging, BCEW = Biogenic Carbon Emission from Combustion of Waste from Renewable Sources Used in Production Processes, CCE = Calcination Carbon Emissions, CCR = Carbonation Carbon Removals, CWNR = Carbon Emissions from Combustion of Waste from Non-Renewable Sources used in Production Processes, GWP-luc = Carbon Emissions from Land-use Change.

per 1 m2 of covered and protected flooring surface for a period of 60 years.

Tech

Indicator	Unit	A1A2A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
BCRP	kg CO2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
BCEP	kg CO2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
BCRK	kg CO2	0.00181	ND	ND	ND	ND	ND	0.00543	ND	ND	ND	ND	ND	ND	ND
BCEK	kg CO2	-0.00181	ND	ND	ND	ND	ND	-0.00543	ND	ND	ND	ND	ND	ND	ND
BCEW	kg CO2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
CCE	kg CO2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
CCR	kg CO2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
CWNR	kg CO2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND

Abbreviations:

BCRP = Biogenic Carbon Removal from Product, BCEP = Biogenic Carbon Emission from Product, BCRK = Biogenic Carbon Removal from Packaging, BCEK = Biogenic Carbon Emission from Packaging, BCEW = Biogenic Carbon Emission from Combustion of Waste from Renewable Sources Used in Production Processes, CCE = Calcination Carbon Emissions, CCR = Carbonation Carbon Removals, CWNR = Carbon Emissions from Combustion of Waste from Non-Renewable Sources used in Production Processes, GWP-luc = Carbon Emissions from Land-use Change.

Scenarios

Transport to the building/construction site (A4)

A4 Module

Fuel Type:	Diesel
Vehicle Type:	Truck and Trailer
Transport Distance:	2.630e+03 km
Capacity Utilization:	33 %
Packaging Mass:	2.713e-02 kg
Gross density of products transported:	1.400e+03 kg/m ³
Weight of products transported:	2.738e-01 kg
Volume of products transported:	1.955e-04 m ³
Capacity utilization volume factor:	1
Assumptions for scenario development:	Transport distance includes finished product to distribution center and distribution center to point of sale.

Installation in to the building/construction site (A5)

A5 Module

Product Lost per Functional Unit:	0.02738 kg
Mass of Packaging Waste Specified by Type:	0.02713 kg
VOC Emissions:	10000000000 ug/m ³
Assumptions for scenario development:	
VOC Assumptions:	The VOC content reported in this EPD is a conservative estimated value and may not accurately represent the actual VOC emissions during the coating's curing process after installation. It is provided for informational purposes only and should not be used as a direct indicator of emissions under actual use conditions

Reference Service Life

B1 Module

RSL:	60 Years
------	----------

Declared Product Properties:

Contributes toward satisfying credit for low emitting material under LEED 4.1. Meets SCAQMD Rule 1113 for VOC content. Meets California Department of Public Health CDPH/EHLB Standard Method Version 1.2 2017. Good Chemical & Abrasion Resistance. Anti-Microbial Agents are available. USDA & FDA Compliant.

Design Application Parameters:

To apply the coating system, begin with Steri-Prime Series / Primer 67LV, which should be applied at 3-4 mils (75-100 microns) using a short-nap mohair roller with a solvent-resistant core, ensuring no puddling occurs; recoat within 6 to 72 hours depending on environmental conditions. Next, apply the first bodycoat of Steri-Coat P at 6-8 mils (150-200 microns) using either a short-nap roller or airless spray, allowing a minimum of 10-12 hours for curing before applying a second bodycoat, with similar application techniques. After the second bodycoat has cured tack-free, a sealer can be applied; consult with a Dudick representative for specific product options and detailed application instructions.

An Assumed Quality of Work, When Installed in Accordance with The Manufacturer's Instructions:

Long term protection is achieved when installed in accordance with manufacturer's instructions. Theoretical coverage is (12-16 mils / 300-400 microns).

Replacement (B4)
B4 Module

Reference Service Life:	60 Years
Replacement Cycle:	5 (ESL/RSL)-1
Further assumptions for scenario development:	Product is assumed to be applied in an industrial environment. A market service lifetime and a technical service lifetime was adopted in the LCA model (see product specifications). Number of recoats is obtained by dividing the service lifetime. One initial coating application and subsequent recoats are required to maintain the average lifespan of a building, assumed to be 60 years.

End of Life
C1 - C4 Modules

Collection Process

Collected with Mixed Construction Waste:	0.2738 kg
--	-----------


Recovery

Landfill:	0.2464 kg
Incineration:	0.02738 kg

Assumptions for scenario development:

Interpretation

Manufacturing of Dudick Inc.'s products involves the direct procurement of raw materials from suppliers. These materials are then transported to Dudick Inc.'s manufacturing facilities where they are stored and mixed to produce the coatings. Notably, the product stage (stage 1) has the highest impact contribution, mainly attributed to the environmental impacts associated with raw material manufacturing. At the application site, coatings are spray or brush applied to various structural components to add a protective barrier to the concrete substrate. The use stage (stage 3) has a smaller contribution to the overall life cycle performance. For the analysis, it was assumed that Dudick's coatings require one initial coating application and multiple recoats to achieve the recommended service life of 60 years, aligning with the building's life cycle. The results were presented per one square meter of covered and protected substrate at a recommended coating thickness. The greatest contribution can be found in the use and maintenance stage due to the effect of the required repaints that will multiply the contribution of the product and design & construction stages together with the product application by the required number of recoats. For one single recoat, production stage, has the highest impact across all impact categories due mainly to the manufacture and transport of raw material, with some contribution of the manufacturing stage. At the application site, coatings are spray or brush applied to various exterior steel structural components to add a protective barrier to the steel substrate. This activity has a smaller contribution to the overall life cycle performance. End-of-life impacts are generally limited because most of the product is assumed to be landfilled, although impacts accumulate at each successive recoating. Given that the raw materials used in product manufacturing have the most significant impact, there are opportunities to substitute these materials with alternatives that have a lower environmental impact or to work with suppliers in order to reduce impact along the supply chain.



Additional Environmental Information

Before using this product, it is recommended that the operator read and follow all caution statements on the product data sheet and on the SDS for this product, and personal protective equipment must be used as directed.

References

- ISO 14044, "Environmental management - Life cycle assessment - Requirements and guidelines", ISO14044:2006.
- ISO 21930, "Sustainability in buildings and civil engineering works Core rules for environmental product declarations of construction products and services", ISO 21930:2017.
- NSF International, Product Category Rule for Environmental Product Declarations for Resinous Floor Coatings, December 2018.
- Bare, J. 2014. Tool for the Reduction and Assessment of Chemical and Other Environmental Impacts (TRACI) TRACI version 2.1 User's Guide. US EPA Office of Research and Development, Washington, DC, EPA/600/R-12/554, <http://nepis.epa.gov/Adobe/PDF/P100HN53.pdf>
- ISO 14025, "Environmental labels and declarations, Type III environmental declarations, Principles and procedures", ISO14025:2006
- US Environmental Protection Agency. Waste Reduction Model (WARM). <https://www3.epa.gov/epawaste/conserve/tools/warm/SWMGHGreport.html>
- Ryberg, M., Vieira, M.D.M., Zgola, M. et al. (2014). 'Updated US and Canadian normalization factors for TRACI 2.1.' Clean Technologies and Environmental Policy 16: 329. doi:10.1007/s10098-013-0629-z
- IPCC, 2013: Climate Change 2013: The Physical Science Basis. Contribution of Working Group I to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change [Stocker, T.F., D. Qin, G.-K. Plattner, M. Tignor, S.K. Allen, J. Boschung, A. Nauels, Y. Xia, V. Bex and P.M. Midgley (eds.)]. Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA, 1535 pp, doi:10.1017/CBO9781107415324
- Ecoinvent v3.9.1, December 2022. The ecoinvent database: Overview and methodology, Data quality guideline for the ecoinvent database version 3, www.ecoinvent.org