



Environmental Product Declaration

Program Operator: Smart EPD®

www.smartepd.com

IN ACCORDANCE WITH EN 15804+A2 AND EN 16810



nora®
by Interface®

SmartEPD-2026-119-1095-01

noraplan® ed 3mm

Date of Issue

Oct 13, 2026

Expiration Date

Oct 13, 2031

Last Updated

Oct 13, 2026



Refer to the EPD Library at www.smartepd.com for the latest EPD listing information

General Information

Interface, Inc.

1280 West Peachtree St NW Atlanta, GA 30309 United States

800-634-6032

sustainability@interface.com

interface.com



Product Name:	noraplan® ed 3mm
Functional Unit:	1 m2
Declaration Number:	SmartEPD-2026-119-1095-01
Date of Issue:	October 13, 2026
Expiration:	October 13, 2031
Last updated:	October 13, 2026
EPD Scope:	Cradle to gate with other options A1 - A3, A4, A5, B2, C1 - C4, D
Market(s) of Applicability:	Europe, United Kingdom of Great Britain and Northern Ireland

General Organization Information

Interface, Inc. is a global flooring solutions company and sustainability leader, offering an integrated portfolio of carpet tile and resilient flooring products — including Interface® carpet tile and LVT, nora® rubber flooring, and FLOR® premium area rugs for commercial and residential spaces. Interface designs and manufactures products with a focus on high performance, innovative design, and environmental responsibility. A pioneer in industrial sustainability for decades, the company is committed to becoming a restorative, carbon-negative enterprise by 2040 and is pursuing verified science-based targets for 2030.

Further information can be found at: www.interface.com

Limitations, Liability and Ownership

Limitations

Exclusions: EPDs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity. EPDs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds – e.g. Type 1 certifications, health assessments and declarations, environmental impact assessments, etc.

Accuracy of Results: EPDs regularly rely on estimations of impacts; the level of accuracy in estimation of effect differs for any particular product line and reported impact.

Comparability: EPDs from different programs may not be comparable. Full conformance with a PCR allows EPD comparability only when all stages of a life cycle have been considered. However, variations and deviations are possible. Example of variations: Different LCA software and background LCI datasets may lead to differences in results for upstream or downstream of the life cycle stages declared.

Liability and Ownership

Reference Standards

Verification Information

External

Product Information

Page 3 / 18

Product Description

In this Environmental Product Declaration (EPD), the resilient rubber floor covering named noraplan® ed with a thickness of 3mm is modelled.

Specific characteristics of the noraplan® ed coverings are:

- Electrostatically dissipative (ed) floorings for optimum ESD protection of electronic devices, equipment and people
- manufacturing method: continuously vulcanized rubber floor coverings in sheets
- covering structure: single-layered
- no addition of PVC, chlorine-containing polymers and phthalate plasticizers
- permanently resilient and wear resistant
- suitable for high traffic areas
- Product SKU(s): NA
- Flooring type: Resilient
- Product thickness: 3 mm
- Product weight: 4380 g/m²
- Product form: Sheet
- Resilient - Rolls width: 1220 mm
- Resilient - Rolls length: 15 m

For the placing on the market of the product in the European Union/European Free Trade Association (EU/EFTA) (with the exception of Switzerland) Regulation (EU) No. 305/2011 (CPR) applies. The product needs a declaration of performance taking into consideration EN 14041:2018-05, Resilient, textile, laminate and modular multilayer floor coverings - Essential characteristics and the CE-marking.

For the application and use the respective national provisions apply.

Further information can be found at: www.interface.com

Product Specifications

Product Classification Codes: oekobau.dat - 6.2.02

Flooring type: Resilient

Table 1. Material Composition

Material/Component Category	Origin	% Mass
Synthetic Rubber	Europe	37
Mineral Fillers	Europe	45
Auxiliary Substances & Vulcanisation System	Europe	15
Colour pigments	Europe	3

Packaging Material	Origin	kg Mass
PE Foil	Europe	0.003

Packaging Material	Origin	kg Mass
Wood Pallet	Europe	0.051
Cardboard	Europe	0.156
Paper	Europe	0.03

Biogenic Carbon Content	kg C per m2
Biogenic carbon content in product	0.51
Biogenic carbon content in accompanying packaging	0.1

Hazardous Materials
No regulated hazardous or dangerous substances are included in this product.

EPD Data Specificity

- Primary Data Year:2025
- Manufacturing Specificity:

✗ Industry Average

✗ Manufacturer Average

✓ Facility Specific

Averaging:
Averaging was not conducted for this EPD

Table 2. System Boundary

Production	A1	Raw material supply	✓
	A2	Transport	✓
	A3	Manufacturing	✓
Construction	A4	Transport to site	✓
	A5	Assembly / Install	✓

Use	B1	Use	ND
	B2	Maintenance	✓
	B3	Repair	ND
	B4	Replacement	ND
	B5	Refurbishment	ND
	B6	Operational Energy Use	ND
	B7	Operational Water Use	ND
End of Life	C1	Deconstruction	✓
	C2	Transport	✓
	C3	Waste Processing	✓
	C4	Disposal	✓
Benefits & Loads Beyond System Boundary	D	Recycling, Reuse Recovery Potential	✓

Note:

ND = Module not declared


Product Composition Diagram

	PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARY
	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
	Raw material supply	Transport	Manufacturing	Transport from gate to site	Assembly/Install	Use	Maintenance	Repair	Replacement	Refurbishment	Building operational energy use during product use	Building operational water use during product use	Deconstruction	Transport	Waste processing	Disposal	Reuse, Recovery, Recycling Potential
EPD Type	X			X	X	ND	X	ND	ND	ND	ND	ND	ND	X	X	X	X

Plants

 nora systems GmbH Höhrnerweg 2-4, Weinheim, Germany

Product Flow Diagram



The production stages are weighing, mixing, and stretching of the unvulcanised blanks on a calender. The following vulcanisation is continuously executed on production lines with steam heated drum or double belt presses, where the sheets are produced under high pressure and at a temperature of approximately 180°C. After the vulcanising machine, the flooring is sanded on the backside and then wound into rolls. The mass per unit area is 4.38 kg/m².

nora systems GmbH purchases the total electrical energy for production and administration at the site Weinheim from renewable energy sources. Respective evidence has been approved by the verifier. Thermal energy is generated centrally and in heating boilers from natural gas.

Our quality and energy management is certified according to *DIN EN ISO 9001* and *DIN EN ISO 50001*.

Software And Database

LCA Software:

☰ Sphera LCA for Experts (formerly GaBi) v. 10.9

LCI Foreground Database(s):

☰ Sphera Managed LCA Content (formerly GaBi Professional Database) v. 2025.1

📍 Europe

LCI Background Database(s):

☰ Sphera Managed LCA Content (formerly GaBi Professional Database) v. 2025.1

📍 Europe

A foreground LCI database is the database used to model the primary, site-specific data collected for this EPD. A background LCI database is the database used to model generic or non-specific data.

Data Quality

Datasets were, if available, taken from the above mentioned MLC 2025.1 database. Further datasets on the upstream chain of the basic material production are approximated with datasets on similar chemicals or are estimated by consolidation of existing datasets and literature information. The data quality can be described as good.

The data quality ranges from good to very good. The temporal quality of the data is very good with both the manufacturing specific data and the LCA FE background data being from 2025.

Life Cycle Module Description

A1–A3: Product Stage

- A1: Raw material extraction and processing, including recycled materials
- A2: Transport of raw and processed materials to manufacturing sites
- A3: Manufacturing at site, including materials, packaging, energy, and waste disposal or recycling. All energy purchased at manufacturing sites is allocated per square meter produced, including offices and warehouses. 100% renewable electricity credits are used for all sites. Waste factor in production. Rubber flooring involves compounding, pressing, vulcanisation, and packaging

A4–A5: Construction Stage

- A4: Transport of finished product to building site
- A5: Installation includes ancillary materials (adhesives), trim waste disposal, and packaging waste. Assumed 5% installation waste for all flooring types. Installation waste sent to incineration or landfill, with energy recovery benefits accounted for in Module D. Industry recommendations followed for adhesive types

B1–B7: Use Stage

- B2: Maintenance effort declared for one year, repeated over the Reference Service Life (RSL). Rubber flooring: machine cleaning (annual), manual cleaning (biweekly).
- Other Use Modules (B1, B3–B7): Not relevant or not declared for these flooring products

C1–C4: End of Life

- C1: Deconstruction process which requires electricity to remove the product from the building at end of life. This requirement is modeled with DE:Electricity grid mix
- C2: Transport of waste to local disposal using diesel truck datasets
- C3: Waste processing for reuse, recovery, or recycling
- C3/1: 100% scenario for incineration with Energy recovery processing which includes an incineration process with an R1-value >0.6
- C3/2: 100% scenario for waste processing through landfill
- C4: Disposal of post-consumer rubber, incineration without energy recovery or landfill
- C4/1: 100% scenario for disposal through the incineration with energy recover
- C4/2: 100% scenario for disposal through landfill

Module D: Benefits and Loads Beyond the System Boundary

- Two end-of-life scenarios are modelled, resulting in two Module D scenarios: Module D/1 and Module D/2
- In Module D/1, the avoided benefits and loads associated with 100% incineration with energy recovery scenario are calculated using RER: Electricity grid mix and RER: Process steam from natural gas as substituted energy sources
- In Module D/2, the avoided benefits and loads associated with 100% landfill scenario are set to zero, as the landfilling of plastics does not result in energy recovery
- Both Module D/1 and Module D/2 scenarios account for avoided benefits and loads from A5, which include recycling, incineration with energy recovery of packaging waste, and incineration with energy recovery of installation waste

<

Electricity accounting methodology:

Market-based

Scenarios

Transport to the building/construction site (A4)

A4 Module

Fuel Type:	Diesel
Liters of Fuel:	0.01 l/100km
Vehicle Type:	Truck
Transport Distance:	500 km
Capacity Utilization:	61 %
Packaging Mass:	0.24 kg
Gross density of products transported:	1460 kg/m ³
Assumptions for scenario development:	Transport is from the factory gate to the place of installation. Thickness of 3mm, 0.0107 kg diesel per 500 km per kg of product and 0.00277 kg Heavy Fuel Oil per 1000 km per kg of product. All values refer to the declared functional unit (1 m ²). Packaging waste and installation waste are considered in subsequent modules (A5, C1–C4).
Fuel Type - Ship:	Heavy Fuel Oil
Transport Distance - Ship:	1000 km
Vehicle Type:	Container ship
Capacity Utilization:	70 %
Liters of Fuel:	0.001 l/100 km

Installation in to the building/construction site (A5)

A5 Module

Installation Scrap Rate Assumed:	5 %
Ancillary Materials:	0.3 kg
Product Lost per Declared/Functional Unit:	0.22 kg
Waste Materials at the Construction Site Before Waste Processing:	0.22 kg
Mass of Packaging Waste Specified by Type:	0.24 kg
Biogenic Carbon Contained in Packaging (kg C):	0.1 kg

Maintenance (B2)

B2 Module

Maintenance Cycle:	3150 Cycles/RSL 7875 Cycles/ESL
Net Fresh Water Consumption Specified by Water Source and Fate:	0.016 m ³
Ancillary Materials Specified by Type:	0.181 kg
Energy Input:	0.27 kWh
Maintenance Process Information:	Cleaning of the floor covering depends on the use of the premises. A kind of 'average' cleaning scenario is assumed following the recommendation of the manufacturer. 1x yearly: machine

intensive cleaning with 250 ml/m² cleaning solution (5% solution); use of single disc machine (1,1 kW, 0,5 h/100 m²) and wet vacuum cleaner (1,0 kW, 0,25 h/100 m²); 2x weekly: manual cleaning with 80 ml/m² cleaning solution (0,5% solution);
RSL = 30 years, ESL = 75 years

Further assumptions for scenario development:

End of Life (C1 - C4)

C1 - C4 Modules

C3/1 & C4/1: 100% Energy Recovery

Collection Process

Collected Separately: 4.68 kg

Recovery

Incineration with Energy Recovery: 4.68 kg

Assumptions for scenario development:

C3/1 – Waste processing (incineration with energy recovery end-of-life): Waste processing by incineration with energy recovery; 100% of the waste mass is treated by incineration in an installation with an R1-value > 0.6. C4/1 – Waste disposal (incineration with energy recovery end-of-life): Final disposal of 100% of the incineration residues in accordance with current disposal practices.

C3/2 & C4/2: 100% Landfill

Collection Process

Collected Separately: 4.68 kg

Recovery

Landfill: 4.68 kg

Disposal

Product or Material for Final Disposal: 4.68 kg

Assumptions for scenario development:

C3/2 – Waste processing (landfill end-of-life): No waste processing is assumed; 100% of the waste mass is sent directly to landfill as the end-of-life scenario. C4/2 – Waste disposal (landfill end-of-life): Final disposal of 100% of the waste mass through landfilling, including landfill operation and management, in accordance with current disposal practices.

Reuse, Recovery and / or Recycling Potentials & Relevant Scenario Information (D)

D Module

Net Energy Benefit from Energy Recovery from Waste Treatment Declared as Export Energy in C3: 5.92 MJ

Net Energy Benefit from Thermal Energy Due to Treatment of Waste Declared as Exported Energy in C4: 10.6 MJ

Process and Conversion Efficiencies:

The assumed scenario in Module D/1 represents 100% incineration with energy recovery processing including an efficiency rate with an R1-value >0.6 In Module D/2, the avoided benefits and loads associated with 100% landfill scenario are set to zero, as the landfilling of the product

Further assumptions for scenario development:

does not result in energy recovery. However, both Module D/1 and Module D/2 scenarios account for avoided benefits and loads from A5, which include recycling, incineration with energy recovery of packaging waste, and incineration with energy recovery of installation waste.

The end-of-life scenarios modeled in Module C and Module D are based on national statistics for flooring to represent real-world scenarios. nora intends for its products to be recycled at end-of-life. For noraplan® rubber floor coverings there are the following options: - Material recycling (e.g. granulating and processing into landing mats, industrial or stable mats, and coverings of sports areas or silent asphalt) - Thermal recycling (e.g. use as substitute fuel in thermal power plants) - Full material and thermal recycling for energy recovery in the cement industry. Use of stored thermal energy as well as use of mineral filler as raw material.

Results

Table 3. Environmental Impact Assessment Results

EF3.1, IPCC AR6 GWP 100, TRACI 2.2, CML 2016 v4.8

per 1 m2 of product.

LCIA results are relative expressions and do not predict impacts on category endpoints, the exceeding of thresholds, safety margins or risks.

Impact Category	Unit	Method	A1 - A3	A4	A5	B2	C1	C2	C3/1	C3/2	C4/1	C4/2	D/1	D/2	D/3
GWP- total	kg CO2 eq	EF3.1	1.52e+1	2.34e-1	1.88e+0	3.31e-1	4.85e-2	1.82e-2	5.28e+0	0	0	1.95e+0	-1.63e+0	-2.12e-1	ND
GWP- fossil	kg CO2 eq	EF3.1	1.73e+1	2.32e-1	1.54e+0	3.21e-1	4.79e-2	1.80e-2	3.46e+0	0	0	1.37e-1	-1.63e+0	-2.11e-1	ND
GWP-biogenic	kg CO2 eq	EF3.1	-2.33e+0	1.47e-3	3.33e-1	9.70e-3	5.71e-4	1.41e-4	1.82e+0	0	0	1.82e+0	0	0	ND
GWP-luluc	kg CO2 eq	EF3.1	2.24e-1	7.89e-4	1.12e-2	8.25e-5	4.04e-5	7.75e-5	5.45e-5	0	0	1.81e-4	-2.57e-3	-9.18e-4	ND
ODP	kg CFC11 eq	EF3.1	3.92e-8	9.60e-14	5.96e-10	2.81e-11	2.25e-12	8.56e-15	5.13e-13	0	0	8.66e-13	-2.60e-11	-2.12e-12	ND
AP	mol H+ eq	EF3.1	4.56e-2	1.61e-3	3.52e-3	1.01e-3	1.07e-4	6.56e-5	3.46e-4	0	0	8.36e-4	-2.29e-3	-5.47e-4	ND
PM	disease incidence	EF3.1	4.47e-7	2.89e-8	3.24e-8	1.29e-8	8.31e-10	4.64e-10	3.27e-9	0	0	8.71e-9	-2.07e-8	-6.32e-9	ND
IRP	kBq U235 eq	EF3.1	4.16e-1	5.69e-4	1.35e-1	1.27e-1	2.02e-3	4.86e-5	3.52e-3	0	0	3.14e-3	-2.34e-1	-1.79e-2	ND
POCP	kg NMVOC eq	EF3.1	4.01e-2	1.70e-3	2.83e-3	9.97e-4	6.07e-5	6.01e-5	2.61e-4	0	0	5.69e-4	-1.87e-3	-5.14e-4	ND
EP-fw	kg P eq	EF3.1	7.19e-5	4.78e-7	6.98e-6	1.09e-5	7.31e-8	4.60e-8	6.20e-8	0	0	7.88e-5	-3.27e-6	-2.66e-6	ND
EP-marine	kg N eq	EF3.1	1.32e-2	7.16e-4	8.66e-4	2.18e-4	3.19e-5	3.07e-5	9.27e-5	0	0	1.81e-4	-7.56e-4	-2.38e-4	ND
EP-terrestrial	mol N eq	EF3.1	1.55e-1	7.82e-3	9.79e-3	1.95e-3	3.83e-4	3.34e-4	1.64e-3	0	0	1.99e-3	-8.25e-3	-2.28e-3	ND
SQI	dimensionless	EF3.1	9.31e+1	6.46e-1	4.75e+0	2.16e-1	2.39e-1	6.34e-2	1.67e-1	0	0	5.10e-1	-1.67e+1	-1.24e+1	ND
WDP	m3 world eq deprived	EF3.1	1.11e+0	8.24e-4	1.82e-1	5.37e-2	1.13e-3	7.36e-5	2.96e-1	0	0	1.71e-2	-1.33e-1	-2.48e-2	ND
ADP-fossil	MJ, net calorific value	EF3.1	3.25e+2	3.00e+0	3.01e+1	7.98e+0	5.56e-1	2.37e-1	5.37e-1	0	0	2.24e+0	-2.73e+1	-3.23e+0	ND
ADP-minerals&metals	kg Sb eq	EF3.1	2.72e-4	1.49e-8	1.39e-5	6.04e-8	1.28e-8	1.31e-9	4.70e-9	0	0	1.09e-8	-2.54e-7	-9.16e-8	ND
ETP-fwio	CTUe	EF3.1	3.29e+2	2.17e+0	2.21e+1	1.46e+0	1.51e-1	1.72e-1	1.98e-1	0	0	1.47e+0	-2.49e+0	-5.24e-1	ND
ETP-fwo	CTUe	EF3.1	4.26e+0	3.30e-1	2.67e-1	4.46e-2	1.01e-1	3.20e-2	6.45e-2	0	0	3.67e+0	-9.61e-1	-2.72e-1	ND
HTP-cio	CTUh	EF3.1	2.09e-9	4.63e-11	1.76e-10	7.19e-11	4.88e-12	3.92e-12	3.38e-12	0	0	6.66e-11	-7.22e-11	-2.33e-11	ND
HTP-co	CTUh	EF3.1	2.42e-9	1.34e-12	1.41e-10	1.81e-11	1.01e-11	1.11e-13	1.63e-11	0	0	5.77e-12	-2.02e-10	-2.00e-11	ND
HTP-ncio	CTUh	EF3.1	9.47e-8	2.17e-9	6.30e-9	6.65e-9	5.92e-10	2.04e-10	1.92e-10	0	0	8.66e-10	-7.32e-9	-2.27e-9	ND
HTP-nco	CTUh	EF3.1	3.26e-9	6.25e-11	3.13e-10	6.35e-11	1.06e-11	5.18e-12	1.57e-11	0	0	4.63e-10	-2.88e-10	-4.95e-11	ND
GWP-total (incl biogenic)	kg CO2 eq	IPCC AR6 GWP 100	1.52e+1	2.34e-1	1.48e+0	3.31e-1	4.85e-2	1.82e-2	3.46e+0	0	0	1.37e-1	-1.35e+0	8.05e-2	ND
GWP-fossil	kg CO2 eq	IPCC AR6 GWP 100	1.74e+1	2.32e-1	1.57e+0	3.23e-1	4.84e-2	1.80e-2	3.46e+0	0	0	1.37e-1	-1.63e+0	-2.12e-1	ND
GWP-biogenic	kg CO2 eq	IPCC AR6 GWP 100	-2.40e+0	1.21e-3	-1.01e-1	7.92e-3	5.96e-5	1.23e-4	-5.45e-5	0	0	-1.81e-4	0	0	ND
GWP-luluc	kg CO2 eq	IPCC AR6 GWP 100	2.24e-1	7.89e-4	1.12e-2	8.25e-5	4.04e-5	7.75e-5	5.45e-5	0	0	1.81e-4	-2.57e-3	-9.18e-4	ND

Impact Category	Unit	Method	A1 - A3	A4	A5	B2	C1	C2	C3/1	C3/2	C4/1	C4/2	D/1	D/2	D/3
ODP	kg CFC 11 eq	TRACI 2.2	5.17e-8	1.22e-13	6.52e-10	5.52e-11	2.77e-12	1.09e-14	6.35e-13	0	0	1.07e-12	-3.22e-11	-2.63e-12	ND
AP	kg SO2 eq	TRACI 2.2	3.97e-2	1.47e-3	3.00e-3	8.47e-4	8.63e-5	5.94e-5	2.73e-4	0	0	7.11e-4	-1.98e-3	-4.71e-4	ND
EP-freshwater	kg P eq	TRACI 2.2	3.52e-5	2.16e-7	3.53e-6	4.90e-6	3.30e-8	2.07e-8	2.80e-8	0	0	4.28e-5	-1.48e-6	-1.20e-6	ND
EP-marine	kg N eq	TRACI 2.2	2.00e-2	1.23e-3	1.32e-3	3.00e-4	4.50e-5	5.11e-5	1.87e-4	0	0	3.09e-4	-1.15e-3	-3.21e-4	ND
POCP	kg O3 eq	TRACI 2.2	6.02e-1	3.84e-2	4.23e-2	1.14e-2	1.33e-3	1.28e-3	5.47e-3	0	0	1.12e-2	-3.89e-2	-1.06e-2	ND
ODP	kg CFC-11 eq	CML 2016 v4.8	5.15e-8	1.22e-13	7.99e-10	5.20e-11	2.77e-12	1.09e-14	6.35e-13	0	0	1.07e-12	-3.22e-11	-2.63e-12	ND
AP	kg SO2 eq	CML 2016 v4.8	5.19e-2	1.14e-3	3.65e-3	8.57e-4	7.69e-5	4.51e-5	2.18e-4	0	0	6.92e-4	-1.74e-3	-3.94e-4	ND
EP	kg PO4 eq	CML 2016 v4.8	2.86e-2	2.55e-4	1.57e-3	1.49e-4	1.77e-5	1.17e-5	4.93e-5	0	0	9.31e-4	-3.53e-4	-1.21e-4	ND
POCP	kg C2H4 eq	CML 2016 v4.8	1.07e-2	-9.72e-5	6.97e-4	2.93e-4	5.09e-6	-1.29e-5	2.19e-5	0	0	6.10e-5	-1.91e-4	-3.92e-5	ND
ADP-fossil	MJ	CML 2016 v4.8	3.17e+2	2.99e+0	2.93e+1	7.49e+0	4.83e-1	2.36e-1	4.70e-1	0	0	2.17e+0	-2.30e+1	-2.88e+0	ND

Note:

Not all abbreviated indicators listed below may be present in the results above. The inclusion of indicators varies based on PCR requirements.

Abbreviations:

GWP = Global Warming Potential, 100 years (may also be denoted as GWP-total, GWP-fossil (fossil fuels), GWP-biogenic (biogenic sources), GWP-luluc (land use and land use change)), ODP = Ozone Depletion Potential, AP = Acidification Potential, EP = Eutrophication Potential, SFP = Smog Formation Potential, POCP = Photochemical oxidant creation potential, ADP-Fossil = Abiotic depletion potential for fossil resources, ADP-Minerals&Metals = Abiotic depletion potential for non-fossil resources, WDP = Water deprivation potential, PM = Particular Matter Emissions, IRP = Ionizing radiation, human health, ETP-fw = Eco-toxicity (freshwater), HTP-c = Human toxicity (cancer), HTP-nc = Human toxicity (non-cancer), SQP = Soil quality index.

Comparisons cannot be made between product-specific or industry average EPDs at the design stage of a project, before a building has been specified. Comparisons may be made between product-specific or industry average EPDs at the time of product purchase when product performance and specifications have been established and serve as a functional unit for comparison. Environmental impact results shall be converted to a functional unit basis before any comparison is attempted. Any comparison of EPDs shall be subject to the requirements of ISO 21930 or EN 15804. EPDs are not comparative assertions and are either not comparable or have limited comparability when they have different system boundaries, are based on different product category rules or are missing relevant environmental impacts. Such comparison can be inaccurate, and could lead to erroneous selection of materials or products which are higher-impact, at least in some impact categories.

Table 4. Resource Use Indicator

per 1 m2 of product.

Indicator	Unit	A1 - A3	A4	A5	B2	C1	C2	C3/1	C3/2	C4/1	C4/2	D/1	D/2	D/3
PERE	MJ	3.62e+1	1.74e-1	5.94e+0	5.80e-1	6.18e-1	1.68e-2	3.52e+1	0	0	4.06e-1	-1.27e+1	-4.88e+0	ND
PERM	MJ	3.71e+1	0	-2.03e+0	0	0	0	-3.51e+1	0	0	0	0	0	ND
PERT	MJ	7.33e+1	1.74e-1	3.91e+0	5.80e-1	6.18e-1	1.68e-2	1.62e-1	0	0	4.06e-1	-1.27e+1	-4.88e+0	ND
PENRE	MJ	1.14e+1	3.00e+0	4.44e+1	7.98e+0	5.56e-1	2.37e-1	2.71e+2	0	0	2.24e+0	-2.73e+1	-3.23e+0	ND
PENRM	MJ	2.87e+2	0	-1.57e+1	0	0	0	-2.71e+2	0	0	0	0	0	ND
PENRT	MJ	2.98e+2	3.00e+0	2.87e+1	7.98e+0	5.56e-1	2.37e-1	5.37e-1	0	0	2.24e+0	-2.73e+1	-3.23e+0	ND
SM	kg	0	0	0	0	0	0	0	0	0	0	0	0	ND
RSF	MJ	0	0	0	0	0	0	0	0	0	0	0	0	ND
NRSF	MJ	0	0	0	0	0	0	0	0	0	0	0	0	ND
FW	m3	5.90e-2	5.65e-5	5.90e-3	1.38e-3	1.87e-4	5.26e-6	6.95e-3	0	0	4.93e-4	-6.29e-3	-1.31e-3	ND
RE	MJ	0	0	8.25e-1	0	0	0	1.65e+1	0	0	0	0	0	ND

Note:

Not all abbreviated indicators listed below may be present in the results above. The inclusion of indicators varies based on PCR requirements.

Abbreviations:

RPRE or PERE = Renewable primary resources used as energy carrier (fuel), RPRM or PERM = Renewable primary resources with energy content used as material, RPRT or PERT = Total use of renewable primary resources with energy content, NRPRE or PENRE = Non-renewable primary resources used as an energy carrier (fuel), NRPRM or PENRM = Non-renewable primary resources with energy content used as material, NRPRRT or PENRT = Total non-renewable primary resources with energy content, SM = Secondary materials, RSF = Renewable secondary fuels, NRSF = Non-renewable secondary fuels, RE = Recovered energy, ADPF = Abiotic depletion potential, FW = Use of net freshwater resources, VOCs = Volatile Organic Compounds.

Table 5. Waste and Output Flow Indicators

per 1 m2 of product.

Indicator	Unit	A1 - A3	A4	A5	B2	C1	C2	C3/1	C3/2	C4/1	C4/2	D/1	D/2	D/3
HWD	kg	7.96e-5	1.36e-10	2.85e-4	4.14e-4	1.47e-9	1.09e-11	3.28e-10	0	0	5.72e-10	-4.10e-8	-2.53e-8	ND
NHWD	kg	2.95e+0	5.05e-4	1.98e-1	1.81e-2	6.00e-4	4.56e-5	1.04e-1	0	0	4.66e+0	-1.73e-2	-5.36e-3	ND
RWD	kg	2.95e-3	4.39e-6	2.97e-4	1.90e-4	2.58e-5	3.72e-7	2.39e-5	0	0	2.42e-5	-1.54e-3	-1.18e-4	ND
CRU	kg	0	0	0	0	0	0	0	0	0	0	0	0	ND
MFR	kg	0	0	1.89e-1	0	0	0	0	0	0	0	0	0	ND
MER	kg	0	0	0	0	0	0	0	0	0	0	0	0	ND
EEE	MJ	0	0	2.77e-1	0	0	0	5.92e+0	0	0	0	0	0	ND
EET	MJ	0	0	5.48e-1	0	0	0	1.06e+1	0	0	0	0	0	ND

Note:

Not all abbreviated indicators listed below may be present in the results above. The inclusion of indicators varies based on PCR requirements.

Abbreviations:

HWD = Hazardous waste disposed, NHWD = Non-hazardous waste disposed, RWD = Radioactive waste disposed, HLRW = High-level radioactive waste, ILLRW = Intermediate- and low-level radioactive waste, CRU = Components for re-use, MFR or MR = Materials for recycling, MER = Materials for energy recovery, MNER = Materials for incineration, no energy recovery, EE or EEE = Recovered energy exported from the product system, EET = Exported thermal energy.

Table 6. Carbon Emissions and Removals

per 1 m2 of product.

Indicator	Unit	A1 - A3	A4	A5	B2	C1	C2	C3/1	C3/2	C4/1	C4/2	D/1	D/2	D/3
BCRP	kg CO2	1.85e+0	0	0	0	0	0	0	0	0	0	0	0	ND
BCEP	kg CO2	0	0	3.71e-2	0	0	0	1.82e+0	0	0	1.82e+0	0	0	ND
BCRK	kg CO2	3.72e-1	0	0	0	0	0	0	0	0	0	0	0	ND
BCEK	kg CO2	0	0	3.72e-1	0	0	0	0	0	0	0	0	0	ND

Note:

Not all abbreviated indicators listed below may be present in the results above. The inclusion of indicators varies based on PCR requirements.

Abbreviations:

BCRP = Biogenic Carbon Removal from Product, BCEP = Biogenic Carbon Emission from Product, BCRK = Biogenic Carbon Removal from Packaging, BCEK = Biogenic Carbon Emission from Packaging, BCEW = Biogenic Carbon Emission from Combustion of Waste from Renewable Sources Used in Production Processes, CCE = Calcination Carbon Emissions, CCR = Carbonation Carbon Removals, CWNr = Carbon Emissions from Combustion of Waste from Non-Renewable Sources used in Production Processes, GWP-luc = Carbon Emissions from Land-use Change.

Interpretation

The life cycle impacts of nora rubber flooring is driven by the Product Stage (A1-A3) and the impacts from this stage are driven by raw materials. Pigments and rubber polymers are the major contributors to impacts. Biobased and recycled materials help in reducing the impacts as compared to virgin petrochemical based materials counterparts.






Table 7. Environmental Activities and Certifications

Certification
Blue Angel

Further Information

For a full list of associated certifications and documentation, please visit interface.com/sustainability.

noraplan ed - all thicknesses

EN 15804+A2 (kg CO2 eq/m2)	2mm	3mm
Climate Change - total	9.78	15.2
Climate Change, fossil	11.3	17.3
Climate Change, biogenic	-1.67	-2.33
Climate Change, luluc	0.146	0.22

References

ISO 14025 Environmental labels and declarations – Type III environmental declarations – Principles and procedures

ISO 14040 Environmental management – Life cycle assessment – Principles and framework

ISO 14044:2006 + Amendments Environmental management – Life cycle assessment – Requirements and guidelines

ISO 21930:2017 Sustainability in buildings and civil engineering works — Core rules for environmental product declarations of construction products and services

EN 15804:2019 + A2 Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products

EN 16810:2017 Resilient, textile and laminate floor coverings – Environmental product declarations – Product category rules

EN ISO 23997 Specifies weight per unit area for flooring products

EN ISO 24346 Specifies thickness for flooring products

EN ISO 10874 Classification of floor coverings for heavy traffic areas

ISO 15686 Reference Service Life calculation (not applied for rubber flooring)

ISO/IEC 25010 Software Product Quality

ISO/IEC 27001 Information Security Management

OWASP SAMM Software Assurance Maturity Model

UL Environment Part A Life Cycle Assessment Calculation Rules and Report Requirements according to ISO 21930:2017, version 4.0

PCR Guidance for Building-Related Products and Services – Part B UL Flooring EPD Requirements, UL 10010-7, v.2, September 2018, Extended to March 31, 2026

EPA Criteria for Product Category Rules (PCRs) To Support the Label Program for Low Embodied Carbon Construction Materials, U.S. Environmental Protection Agency, 2024

LCA FE (GaBi) 10.9.0.31 (2024) Software-System and Databases for Life Cycle Engineering (Sphera)

Sphera LCA FE databases Used for secondary data and modelling

Environmental Footprint (EF) 3.1 Characterisation factors (European Commission JRC, 2022)

TRACI 2.2 Tool for the Reduction and Assessment of Chemicals and other Environmental Impacts (US EPA, 2021)

CML 2001 Operational guide to the ISO standards (Guinee et al.), Centre for Milieukunde (CML) Leiden

ERASM, FEFCO, Plastics Europe Industry associations for secondary data

UL Environment PCRs (Part A and Part B) For EPD creation and verification

ACLCA PCR Open Standard Guidance for Quantifying Renewable Electricity Instruments in Environmental Product Declarations. ACLCA. 2022

ELCD European Commission Joint Research Center (2008). LCA Tools, Services and Data

Frischknecht, Rolf (2009) LCI modelling approaches applied on recycling of materials

US EPA (2024) C-MORE EPD Criteria for Data Quality and Transparency

ISO/TR 14047 Examples of impact categories and mechanisms